

# CSM-708S12 Versatile Spring Former



Working Range 加工線材範圍	Basic Wire Diameter 基本線材加工	0.13~0.8 mm
Working Ability 加工能力	O.D.Max 最大外徑	20 mm
	Leg Length 最大足長	20 mm
Forming(1 - 8)-Axis 成型軸	Range of Angle Value 角度值範圍	1 - 2000
	Max. Rotation Value 最高轉速	90 RPM
Feeding Axis 送線軸	Range of Feeding Value 送線值範圍	0.01 - 99999.99 mm
	Max. Feeding Speed 最大送線速度	90 M/min
Rotary Quill Axis 轉芯軸	Range of Angle Value 角度值範圍	1 - 4000
Servo Spinner Axis 捲曲軸	Range of Angle Value 角度值範圍	1 - 36000
Control System 控制系統	Program Storage 可記憶程式數	5000 PROGRAMS
	Number Of Axes 軸數	標準10軸(可擴充至12軸)
Power Supply 動力	Power Supply 電源供應	200/220 3Φ 50/60Hz 4.5KVA
	Motor Capacity 馬達規格	成型軸R2AA06040 - 0.4Kw * 8 ; 送線軸R2AAB8100 - 1.0Kw * 1 ; 轉芯軸R2AA06040 - 0.4Kw * 1 ; 捲曲軸R2AA06020 - 0.2Kw (選購)
Machine Scale 機械度量	Dimension(WxHxL) 尺寸(寬高長)	129(W) x159(H) x 89(L) cm
	Weight 重量	620 Kg

● SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE 規格以實機為準